
| DATE | REV | REVISION RECORD | AUTH. | DR. | CK. |
|---|---|---|---|---|---|
| 5.18.05 | A | ADDED CDOM TO TABLE | CB | KLP | |
| 7.23.09 | B | ECN 1247: CHANGED CABLE TYPE | CB | PC | |




| SBE PN | DIM A |
|---|---|
| 171831 | 60 INCHES |
| 172029 | 24 INCHES |
| 172788 | 42 INCHES |
| | |

| P1 (MCIL-6FS) | P2 (AG-206) | SIGNAL |
|---|---|---|
| PIN 1 | PIN 1,5 | POWER COMMON |
| PIN 2 | PIN 2 | SEAPOINT SIGNAL |
| PIN 3 | PIN 3 | SEAPOINT GROUND |
| PIN 4 | --- | --- |
| PIN 5 | --- | --- |
| PIN 6 | PIN 4 | +15 VDC |

| SEAPOINT | GAIN | RANGE |
|---|---|---|
| TURBIDITY | 5X | 500 FTU |
| FLUOROMETER | 3X | 50 µg/L |
| CDOM (SUVF) | 3X | 500 µg/L |

| | | | | |
|---|---|---|---|---|
| TOLERANCES | SEA-BIRD ELECTRONICS, INC | | | |
| FRACTIONAL | P/N SEE TABLE | SCALE NTS | DRAWN BY KH | APPROVED BY |
| DECIMAL | TITLE CABLE: AG-206 TO MCIL-6FS SEAPOINT (5X/3X) | | | |
| ANGULAR | DATE 11.12.20004 | DRAWING NUMBER 32849 | | REV B |