
| DATE | SYM | REVISION RECORD | AUTH. | DR. | CK. |
|---|---|---|---|---|---|
| | | | | | |




| SBE PN | DIM A | DIM B | DIM C |
|---|---|---|---|
| 172519 | 1 METER | 1 METER | 1 METER |
| | | | |

| P1 AG-206 | P2 RMG-4FS | P3 AG-206 | FUNCTION |
|---|---|---|---|
| PIN 1 | PIN 1 | PIN 1 | PWR COMMON |
| PIN 2 | | PIN 2 | SEAPOINT SIG. |
| PIN 3 | | PIN 3 | SEAPOINT COM. |
| PIN 4 | PIN 2 | | OXYGEN SIGNAL |
| PIN 5 | PIN 3 | | OXYGEN COMMON |
| PIN 6 | PIN 4 | PIN 4 | POWER (+) |

| SEAPOINT | GAIN | RANGE |
|---|---|---|
| TURBIDITY METER | 100X | 25 FTU |
| FLUOROMETER | 30X | 5 µg/l |
| CDOM (SUVF) | 30X | 50 µg/l |

SEA-BIRD ELECTRONICS, INC

| P/N | SCALE | DRAWN BY | CB |
|---|---|---|---|
| SEE TABLE | NTS | APPROVED BY | CB |

Y-CABLE: SBE43 & SEAPOINT (100X/30X)

| DATE | DWG NO. | SHEET | REV |
|---|---|---|---|
| 5/11/09 | 33430 | 1 of 1 | |